

SPOTLIGHT

SPOTLIGHT LIDER A 957 27W 60° WHITE SPECIAL ON/OFF

Article number: N004-K0003-CC957-H5-G60-ZE53_700-S1-###



LED	COB	Spotlight
Light colour	5700 [K] SPECIAL	Track more possible. on enquir power is 3
CRI	90	
Led chip flux	3484 [lm]	
Luminous flux	3135 [lm]	
System power	27 [W]	
Luminaire Efficiency	116 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: Al

WHITE

Plastic

220-240V 50-60Hz

nt LED

nounted LED spotlight. Aluminium housing. Ceiling base installation Available in white, black and grey. Any RAL palette colour available iry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum § 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska