

SPOTLIGHT

SPOTLIGHT LIDER A 930 19W 23° WHITE CRI97 ON/OFF

Article number: N004-K0003-HI930-H5-G23-ZE53_500-S1-###



| LED | COB | Spotlight LED |
|----------------------|----------------|--|
| Light colour | 3000 [K] CRI97 | Track mounted L possible. Availab on enquiry. Refle power is 31W. |
| CRI | 90 | |
| Led chip flux | 2199 [lm] | |
| Luminous flux | 1979 [lm] | |
| System power | 19 [W] | |
| Luminaire Efficiency | 104 [lm/W] | |
| Beam angle | 23° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024