

SPOTLIGHT

SPOTLIGHT LIDER A 827 23W 60° WHITE | ON/OFF

Article number: N004-K0003-RF827-H5-G60-ZE53_600-S1-###



| LED | COB | Spotlig |
|-----------------------------------|---------------------|---------------------------------------|
| Light colour | 2700 [K] | Track r possibl on enq power |
| CRI | 80 | |
| Led chip flux | 3233 [lm] | |
| Luminous flux System power | 2909 [lm] 23 [W] | |
| | | |
| Luminaire Efficiency | 126 [lm/W] | |
| Beam angle | 60° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | Note: |

WHITE

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024