

SPOTLIGHT

SPOTLIGHT LIDER A 830 21W 15° WHITE | ON/OFF

Article number: N004-K0003-RF830-H5-G15-ZE53_550-S1-###



LED	COB	Spotlight I
Light colour	3000 [K]	Track mour possible. A on enquiry. power is 31
CRI	80	
Led chip flux	2994 [lm]	
Luminous flux	2694 [lm]	
System power	21 [W]	
Luminaire Efficiency	128 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All

WHITE

Plastic

220-240V 50-60Hz

LED

unted LED spotlight. Aluminium housing. Ceiling base installation Available in white, black and grey. Any RAL palette colour available y. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska