

SPOTLIGHT

SPOTLIGHT LIDER A 830 25W 45° WHITE | ON/OFF

Article number: N004-K0003-RF830-H5-G45-ZE53_650-S1-###



LED	COB	Spotlight LED
Light colour	3000 [K]	Track mounted possible. Availa on enquiry. Ref power is 31W.
CRI	80	
Led chip flux	3538 [lm]	
Luminous flux	3184 [lm]	
System power	25 [W]	
Luminaire Efficiency	127 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All data

WHITE

Plastic

220-240V 50-60Hz

D

ed LED spotlight. Aluminium housing. Ceiling base installation ilable in white, black and grey. Any RAL palette colour available eflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska