

## SPOTLIGHT LIDER A 830 14W 60° WHITE | ON/OFF

Article number: N004-K0003-RF830-H5-G60-ZE53\_350-S1-###





L	Ξ	D	J	C	)	В

Light colour 3000 [K] |

CRI 80

Led chip flux 1905 [lm]

Luminous flux 1714 [lm]

System power 14 [W]

Luminaire Efficiency 122 [lm/W]

Beam angle 60°

Controller ON/OFF

MacAdam 3 SDCM

## **Spotlight LED**

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

## **LUMINAIRE**

Weight 0.7 [kg]

Protection rating IP , IK , class IP 20, IK 01,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.









