

## SPOTLIGHT

## SPOTLIGHT LIDER A 830 21W 60° WHITE | ON/OFF

Article number: N004-K0003-RF830-H5-G60-ZE53\_550-S1-###



LED	COB	Spotlig
Light colour	3000 [K]	Track m possible on enqu power is
CRI	80	
Led chip flux	2994 [lm]	
Luminous flux	2694 [lm]	
System power	21 [W]	
Luminaire Efficiency	128 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: /

WHITE

Plastic

220-240V 50-60Hz

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024