

## SPOTLIGHT

## SPOTLIGHT LIDER A 835 19W 38° WHITE | ON/OFF

Article number: N004-K0003-RF835-H5-G38-ZE53\_500-S1-###



LED	COB	Sp
Light colour	3500 [K]	Tra pos on pov
CRI	80	
Led chip flux	2783 [Im] 2504 [Im] 19 [W] 132 [Im/W]	
Luminous flux		
System power		
Luminaire Efficiency		
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

**OPTIONS** 

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024