

SPOTLIGHT

SPOTLIGHT LIDER A 840 31W 15° WHITE | ON/OFF

Article number: N004-K0003-RF840-H5-G15-ZE53_800-S1-###



LED	COB	Sp		
Light colour	4000 [K]	Tra		
CRI	80 4542 [lm] 4087 [lm] 31 [W] 132 [lm/W]	pos on pov		
Led chip flux Luminous flux System power Luminaire Efficiency				
			Beam angle	15°
		Controller	ON/OFF	
MacAdam	3 SDCM			
LUMINAIRE				
Weight	0,7 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,	Ν		

WHITE

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024