

SPOTLIGHT

SPOTLIGHT LIDER A 840 25W 38° WHITE | ON/OFF

Article number: N004-K0003-RF840-H5-G38-ZE53_650-S1-###



LED	COB	Sp		
Light colour	4000 [K]	Tra		
CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle	80 3690 [lm] 3321 [lm] 25 [W] 133 [lm/W] 38°	po; po;		
			Controller	ON/OFF
		MacAdam	3 SDCM	
		LUMINAIRE		_
Weight	0,7 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,	Ν		

WHITE

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024