

SPOTLIGHT

SPOTLIGHT LIDER A 927 21W 23° WHITE | ON/OFF

Article number: N004-K0003-RF927-H5-G23-ZE53_550-S1-###



| LED | COB | Spotlight LED |
|-----------------------------------|--------------|---|
| Light colour | 2700 [K] | Track mounted possible. Availal on enquiry. Refl power is 31W. |
| CRI | 80 | |
| Led chip flux | 2444 [lm] | |
| Luminous flux | 2199 [lm] | |
| System power | 21 [W] | |
| Luminaire Efficiency | 105 [lm/W] | |
| Beam angle | 23° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | Note: All data |

WHITE

Plastic

220-240V 50-60Hz

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024