

SPOTLIGHT

SPOTLIGHT LIDER A 927 19W 38° WHITE | ON/OFF

Article number: N004-K0003-RF927-H5-G38-ZE53_500-S1-###



LED	COB	Spo				
Light colour CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	2700 [K] 80 2222 [lm] 1999 [lm] 19 [W] 105 [lm/W] 38° ON/OFF 3 SDCM	Trac pos on e pow				
				LUMINAIRE		_
				Weight	0,7 [kg]	
		Protection rating IP , IK , class	IP 20, IK 1,	N		

WHITE

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024