

SPOTLIGHT

SPOTLIGHT LIDER A 930 19W 23° WHITE | ON/OFF

Article number: N004-K0003-RF930-H5-G23-ZE53_500-S1-###



LED	СОВ	Spotligh
Light colour	3000 [K]	Track m possible on enqui power is
CRI	90	
Led chip flux	2305 [lm]	
Luminous flux	2074 [lm]	
System power	19 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	23°	
Controller	ON/OFF	
MacAdam	3 SDCM	
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024