

SPOTLIGHT LIDER A 930 23W 45° WHITE | ON/OFF

Article number: N004-K0003-RF930-H5-G45-ZE53_600-S1-###





| LED | COB |
|----------------------|------------|
| Light colour | 3000 [K] |
| CRI | 90 |
| Led chip flux | 2767 [lm] |
| Luminous flux | 2490 [lm] |
| System power | 23 [W] |
| Luminaire Efficiency | 108 [lm/W] |
| Beam angle | 45° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight 0,7 [kg]

Protection rating IP, IK, class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 21.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska