

SPOTLIGHT

SPOTLIGHT LIDER A 940 31W 15° WHITE | ON/OFF

Article number: N004-K0003-RF940-H5-G15-ZE53_800-S1-###



| LED | COB | Spotlight LED |
|-----------------------------------|--------------|---|
| Light colour | 4000 [K] | Track mounted LED s possible. Available in on enquiry. Reflector power is 31W. |
| CRI | 90 | |
| Led chip flux | 3866 [lm] | |
| Luminous flux | 3479 [lm] | |
| System power | 31 [W] | |
| Luminaire Efficiency | 112 [lm/W] | |
| Beam angle | 15° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | Note: All data are ty |

WHITE

Plastic

220-240V 50-60Hz

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024