

SPOTLIGHT

SPOTLIGHT LIDER A 940 10W 45° WHITE | ON/OFF

Article number: N004-K0003-RF940-H5-G45-ZE63_250-S1-###



LED	COB	Spotligh
Light colour	4000 [K]	Track mo possible. on enqui power is
CRI	90	
Led chip flux	1208 [lm]	
Luminous flux	1087 [lm]	
System power	10 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: A

WHITE

Plastic

220-240V 50-60Hz

ht LED

nounted LED spotlight. Aluminium housing. Ceiling base installation e. Available in white, black and grey. Any RAL palette colour available uiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum s 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska