

## SPOTLIGHT LIDER A 825 10W 15° WHITE BREAD ON/OFF

Article number: N004-K0003-VF825-H5-G15-ZE63\_250-S1-###



|                      |                |
|----------------------|----------------|
| LED                  | COB            |
| Light colour         | 2500 [K] BREAD |
| CRI                  | 80             |
| Led chip flux        | 1195 [lm]      |
| Luminous flux        | 1075 [lm]      |
| System power         | 10 [W]         |
| Luminaire Efficiency | 108 [lm/W]     |
| Beam angle           | 15°            |
| Controller           | ON/OFF         |
| MacAdam              | 3 SDCM         |

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 0,7 [kg]         |
| Protection rating IP , IK , class | IP 20, IK 1,     |
| Luminaire colour                  | WHITE            |
| Cover                             | Plastic          |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 23.06.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska