

SPOTLIGHT

SPOTLIGHT LIDER A 825 31W 23° WHITE BREAD ON/OFF

Article number: N004-K0003-VF825-H5-G23-ZE53_800-S1-###



LED	COB	Spo			
Light colour	2500 [K] BREAD	Tra			
CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	80 3621 [lm] 3258 [lm] 31 [W] 105 [lm/W] 23° ON/OFF 3 SDCM	pos on é pow			
			LUMINAIRE		-
			Weight	0,7 [kg]	
			Protection rating IP , IK , class	IP 20, IK 1,	N

WHITE

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.06.2024