

SPOTLIGHT

SPOTLIGHT LIDER A 825 21W 38° WHITE BREAD ON/OFF

Article number: N004-K0003-VF825-H5-G38-ZE53_550-S1-###



LED	COB	Spotli
Light colour	2500 [K] BREAD	Track possib on end power
CRI	80	
Led chip flux	2574 [lm]	
Luminous flux	2316 [lm]	
System power	21 [W]	
Luminaire Efficiency	110 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

Spotlight LED

rack mounted LED spotlight. Aluminium housing. Ceiling base installation ossible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ower is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.06.2024