

## SPOTLIGHT

## SPOTLIGHT LIDER A 825 21W 45° WHITE BREAD ON/OFF

Article number: N004-K0003-VF825-H5-G45-ZE53\_550-S1-###



LED	СОВ	Spotlight L
Light colour	2500 [K] BREAD	Track moun possible. Av on enquiry. power is 31 <sup>1</sup>
CRI	80	
Led chip flux	2574 [lm]	
Luminous flux	2316 [lm]	
System power	21 [W]	
Luminaire Efficiency	110 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All d

WHITE

Plastic

220-240V 50-60Hz

## LED

Inted LED spotlight. Aluminium housing. Ceiling base installation Available in white, black and grey. Any RAL palette colour available 6. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska