

SPOTLIGHT

SPOTLIGHT LIDER B 835 21W 45° GREY | ON/OFF

Article number: N005-K0001-RF835-H5-G45-ZA02_550-S1-AA1



LED	COB	Spotlight LED
Light colour	3500 [K]	Track mounted LED spotligh possible. Available in white, on enquiry. Reflector beams power is 31W.
CRI	80	
Led chip flux	3061 [lm]	
Luminous flux	2754 [lm]	
System power	21 [W]	
Luminaire Efficiency	131 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		
Weight	0,8 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All data are typical v

GREY

Plastic

220-240V 50-60Hz

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024