

## SPOTLIGHT

## SPOTLIGHT LIDER B 930 14W 15° GREY | ON/OFF

Article number: N005-K0001-RF930-H5-G15-ZA01\_350-S1-AA1



LED	COB	Spotlight
Light colour	3000 [K]	Track mou
CRI	90 1613 [lm] 1451 [lm]	possible. A on enquiry power is 3
Led chip flux		
Luminous flux		
System power	14 [W]	
Luminaire Efficiency	104 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

## LED

unted LED spotlight. Aluminium housing. Ceiling base installation Available in white, black and grey. Any RAL palette colour available y. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

**OPTIONS** 

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska