

SPOTLIGHT

SPOTLIGHT LIDER B 930 25W 15° BLACK CRI97 ON/OFF

Article number: N005-K0002-HI930-H5-G15-ZA02_650-S1-AA2



| LED | COB | S |
|----------------------|----------------|----------------|
| Light colour | 3000 [K] CRI97 | Т |
| CRI | 90 | po or po |
| Led chip flux | 2797 [lm] | |
| Luminous flux | 2517 [lm] | |
| System power | 25 [W] | |
| Luminaire Efficiency | 101 [lm/W] | |
| Beam angle | 15° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |

0.8 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 14.08.2024