

SPOTLIGHT LIDER B 930 25W 45° BLACK CRI97 ON/OFF

Article number: N005-K0002-HI930-H5-G45-ZA02_650-S1-AA2





LED COB

Light colour 3000 [K] CRI97

CRI 9

Led chip flux 2797 [lm]

Luminous flux 2517 [lm]

System power 25 [W]

Luminaire Efficiency 101 [lm/W]

Beam angle 45°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

 Weight
 0,8 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 BLACK

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska