

## SPOTLIGHT

## SPOTLIGHT LIDER B 840 23W 15° BLACK | ON/OFF

Article number: N005-K0002-RF840-H5-G15-ZA02\_600-S1-AA2



LED	COB	Spotligh
Light colour	4000 [K]	Track mo possible on enqui power is
CRI	80	
Led chip flux	3407 [lm]	
Luminous flux	3066 [lm]	
System power	23 [W]	
Luminaire Efficiency	[Im/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.09.2024