

## SPOTLIGHT

## SPOTLIGHT LIDER B 840 14W 38° BLACK | ON/OFF

Article number: N005-K0002-RF840-H5-G38-ZA01\_350-S1-AA2



LED	СОВ	Spotligh
Light colour	4000 [K]	Track mo possible. on enquir power is
CRI	80	
Led chip flux	1987 [lm]	
Luminous flux	1788 [lm]	
System power	14 [W]	
Luminaire Efficiency	128 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,8 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz

## ht LED

nounted LED spotlight. Aluminium housing. Ceiling base installation e. Available in white, black and grey. Any RAL palette colour available uiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum s 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

**OPTIONS** 

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska