

SPOTLIGHT

SPOTLIGHT LIDER B 840 21W 45° BLACK | ON/OFF

Article number: N005-K0002-RF840-H5-G45-ZA02_550-S1-AA2



LED	COB	Spotlight LE
Light colour	4000 [K]	Track mounte possible. Ava on enquiry. R power is 31W
CRI	80	
Led chip flux	3122 [lm]	
Luminous flux	2809 [lm]	
System power	21 [W]	
Luminaire Efficiency	134 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,8 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz

ED

ted LED spotlight. Aluminium housing. Ceiling base installation railable in white, black and grey. Any RAL palette colour available Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska