

## SPOTLIGHT

## SPOTLIGHT LIDER B 930 19W 38° WHITE HI EFFICIENT ON/OFF

Article number: N005-K0003-BB930-H5-G38-ZA01\_500-S1-AA3



LED	СОВ
Light colour	3000 [K] HI EFFICIENT
CRI	
Led chip flux	90
	3184 [lm]
Luminous flux	2865 [lm]
System power	6. <i>3</i>
Luminaire Efficiency	19 [W]
Beam angle	151 [lm/W]
	38°
Controller	ON/OFF
MacAdam	
	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

## LUMINAIRE

Weight	0,8 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024