

SPOTLIGHT LIDER B 940 19W 15° WHITE HI EFFICIENT ON/OFF

Article number: N005-K0003-BB940-H5-G15-ZA01_500-S1-AA3



ON/OFF

3 SDCM



COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 3189 [lm] Luminous flux 2870 [lm] System power 19 [W] Luminaire Efficiency 151 [lm/W] Beam angle 15° Controller

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

MacAdam

Weight 0,8 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska