

SPOTLIGHT

SPOTLIGHT LIDER B 827 19W 60° WHITE | ON/OFF

Article number: N005-K0003-RF827-H5-G60-ZA01_500-S1-AA3



LED	COB	Spotlight LED
Light colour	2700 [K]	Track mounted LED sp possible. Available in v on enquiry. Reflector b
CRI	80	
Led chip flux	2694 [lm]	power is 31W.
Luminous flux	2424 [lm]	
System power	19 [W]	
Luminaire Efficiency	128 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	
JMINAIRE		_
Weight	0,8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

spotlight. Aluminium housing. Ceiling base installation white, black and grey. Any RAL palette colour available beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska