

SPOTLIGHT

SPOTLIGHT LIDER B 850 14W 38° WHITE | ON/OFF

Article number: N005-K0003-RF850-H5-G38-ZA01_350-S1-AA3



LED	COB	Spotlight LED
Light colour	5000 [K]	Track mounted L possible. Availab on enquiry. Refle power is 31W.
CRI	80	
Led chip flux	2027 [lm]	
Luminous flux	1824 [lm]	
System power	14 [W]	
Luminaire Efficiency	130 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		
Weight	0.8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 14.08.2024