

SPOTLIGHT

SPOTLIGHT LIDER B 850 25W 45° WHITE | ON/OFF

Article number: N005-K0003-RF850-H5-G45-ZA02_650-S1-AA3



LED	COB	Spotlight LED
Light colour	5000 [K]	Track mounted LED spot possible. Available in whi on enquiry. Reflector bea power is 31W.
CRI	80	
Led chip flux	3764 [lm]	
Luminous flux	3387 [lm]	
System power	25 [W]	
Luminaire Efficiency	135 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		_
Weight	0,8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

otlight. Aluminium housing. Ceiling base installation hite, black and grey. Any RAL palette colour available eams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

Cover

Protection rating IP , IK , class

Operating voltage

Luminaire colour

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska