

SPOTLIGHT

SPOTLIGHT LIDER B 930 25W 15° WHITE | ON/OFF

Article number: N005-K0003-RF930-H5-G15-ZA02_650-S1-AA3



LED	СОВ	Spotlight LED
Light colour	3000 [K]	Track mounted LED s
CRI	90	possible. Available in on enquiry. Reflector
Led chip flux	2997 [lm]	power is 31W.
Luminous flux	2697 [lm]	
System power	25 [W]	
Luminaire Efficiency	108 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
JMINAIRE		
Weight	0,8 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024