

## SPOTLIGHT

## SPOTLIGHT LIDER B 825 14W 23° WHITE BREAD ON/OFF

Article number: N005-K0003-VF825-H5-G23-ZA01\_350-S1-AA3



| LED                  | COB            | Spotlight LED  |
|----------------------|----------------|--|
| Light colour         | 2500 [K] BREAD | Track mounted Ll<br>possible. Availabl<br>on enquiry. Refle<br>power is 31W. |
| CRI                  | 80             |  |
| Led chip flux        | 1674 [lm]      |  |
| Luminous flux        | 1506 [lm]      |  |
| System power         | 14 [W]         |  |
| Luminaire Efficiency | 108 [lm/W]     |  |
| Beam angle           | 23°            |  |
| Controller           | ON/OFF         |  |
| MacAdam              | 3 SDCM         |  |
| UMINAIRE             |                |  |
| Weight               | 0,8 [kg]       |  |

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

rack mounted LED spotlight. Aluminium housing. Ceiling base installation ossible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ower is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024