


SPOTLIGHT

SPOTLIGHT LIDER D MINIS 835 27W 15° GREY | ON/OFF

Article number: N006-K0001-RF835-H5-M15-ZE51_700-S2-AA1



180 mm
Ø 86 mm

LED	COB	Spo
Light colour	3500 [K]	Cor inst cold 60°
CRI	80	
Led chip flux	3896 [lm]	
Luminous flux	3506 [lm]	
System power	27 [W]	
Luminaire Efficiency	130 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,81 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

ootlight LED

ompact track mounted LED spotlight. Aluminium housing. Ceiling base stallation possible. Available in white, black and grey. Any RAL palette slour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and ^o. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska