

SPOTLIGHT

SPOTLIGHT LIDER D MINIS 930 23W 23° BLACK | ON/OFF

Article number: N006-K0002-RF930-H5-M23-ZE52_600-S2-AA2



0,81 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz



LUMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	23°
Luminaire Efficiency	108 [lm/W]
System power	23 [W]
Luminous flux	2490 [lm]
Led chip flux	2767 [lm]
CRI	90
Light colour	3000 [K]
LED	COB

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

L

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024