

## SPOTLIGHT

## SPOTLIGHT LIDER D MINIS 940 14W 60° BLACK | ON/OFF

Article number: N006-K0002-RF940-H5-M60-ZE52\_350-S2-AA2



0,81 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz



LED	СОВ
Light colour	4000 [K]
CRI	90
Led chip flux	1691 [lm]
Luminous flux	1521 [lm]
System power	14 [W]
Luminaire Efficiency	109 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Weight

Luminaire colour

Operating voltage

L

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024