

SPOTLIGHT LIDER B MINI 957 14W 15° GREY SPECIAL ON/OFF

Article number: N007-K0001-CC957-H5-M15-ZE51_350-S1-###



3 SDCM



COB

5700 [K] SPECIAL Light colour

CRI

Led chip flux 1820 [lm] Luminous flux 1638 [lm] System power 14 [W] Luminaire Efficiency 117 [lm/W] Beam angle 15° Controller ON/OFF

LUMINAIRE

MacAdam

0,85 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska