

SPOTLIGHT

SPOTLIGHT LIDER B MINI 957 23W 45° GREY SPECIAL ON/OFF

Article number: N007-K0001-CC957-H5-M45-ZE51_600-S1-###





| LED | COB | Spotlight LE |
|----------------------|------------------|---|
| Light colour | 5700 [K] SPECIAL | Compact trac installation po colour availat 60°. Maximur |
| CRI | 90 | |
| Led chip flux | 3023 [lm] | |
| Luminous flux | 2720 [lm] | |
| System power | 23 [W] | |
| Luminaire Efficiency | 118 [lm/W] | |
| Beam angle | 45° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| | 0.95 [kg] | |
| Weight | 0,85 [kg] | |

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

ED

ack mounted LED spotlight. Aluminium housing. Ceiling base able on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and um power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska