

SPOTLIGHT LIDER B MINI 930 21W 15° GREY CRI97 ON/OFF

Article number: N007-K0001-HI930-H5-M15-ZE51_550-S1-###



COB

15°



3000 [K] CRI97 Light colour CRI 2402 [lm] Led chip flux Luminous flux 2161 [lm] System power 21 [W] Luminaire Efficiency 103 [lm/W]

Beam angle Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

0,85 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska