

## SPOTLIGHT LIDER B MINI 930 25W 23° GREY CRI97 ON/OFF

Article number: N007-K0001-HI930-H5-M23-ZE51\_650-S1-###



COB

23°



3000 [K] CRI97 Light colour CRI Led chip flux 2797 [lm] Luminous flux 2517 [lm] System power 25 [W] Luminaire Efficiency 101 [lm/W]

Beam angle Controller ON/OFF MacAdam 3 SDCM

## **LUMINAIRE**

0,85 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska