

SPOTLIGHT LIDER B MINI 930 25W 45° GREY CRI97 ON/OFF

Article number: N007-K0001-HI930-H5-M45-ZE51_650-S1-###





CRI 90 installation possible. colour available on e	LED	COB	Spotlight LED
CH90colour available on e 60°. Maximum powerLed chip flux2797 [Im]Luminous flux2517 [Im]System power25 [W]Luminaire Efficiency101 [Im/W]Beam angle45°ControllerON/OFFMacAdam3 SDCM	Light colour	3000 [K] CRI97	Compact track mounte installation possible. A colour available on enc 60°. Maximum power i
Led chip hux2/9/ [m]Luminous flux2517 [m]System power25 [W]Luminaire Efficiency101 [lm/W]Beam angle45°ControllerON/OFFMacAdam3 SDCM	CRI	90	
System power 25 [W] Luminaire Efficiency 101 [Im/W] Beam angle 45° Controller ON/OFF MacAdam 3 SDCM	Led chip flux	2797 [lm]	
Luminaire Efficiency 101 [lm/W] Beam angle 45° Controller ON/OFF MacAdam 3 SDCM	Luminous flux	2517 [lm]	
Beam angle 45° Controller ON/OFF MacAdam 3 SDCM	System power	25 [W]	
Controller ON/OFF MacAdam 3 SDCM	Luminaire Efficiency	101 [lm/W]	
MacAdam 3 SDCM	Beam angle	45°	
LUMINAIRE	Controller	ON/OFF	
	MacAdam	3 SDCM	
Weight 0,85 [kg]	LUMINAIRE		
	Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

ted LED spotlight. Aluminium housing. Ceiling base Available in white, black and grey. Any RAL palette nquiry. Reflector beams available: 15°, 23°, 38°, 45° and is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska