

SPOTLIGHT LIDER B MINI 830 25W 45° GREY | ON/OFF

Article number: N007-K0001-RF830-H5-M45-ZE51_650-S1-###





LED	COB	Spotlight LED
Light colour	3000 [K]	Compact track n installation possi colour available 60°. Maximum p
CRI	80	
Led chip flux	3538 [lm]	
Luminous flux	3184 [lm]	
System power	25 [W]	
Luminaire Efficiency	127 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

mounted LED spotlight. Aluminium housing. Ceiling base sible. Available in white, black and grey. Any RAL palette e on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT