

SPOTLIGHT LIDER B MINI 840 23W 15° GREY | ON/OFF

Article number: N007-K0001-RF840-H5-M15-ZE51_600-S1-###





LED	COB	Spotlight LE
Light colour	4000 [K]	Compact tracl installation po colour availab 60°. Maximun
CRI	80	
Led chip flux	3407 [lm]	
Luminous flux	3066 [lm] 23 [W]	
System power		
Luminaire Efficiency	133 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

ED

ck mounted LED spotlight. Aluminium housing. Ceiling base able on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and um power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT

