

SPOTLIGHT LIDER B MINI 927 25W 15° GREY | ON/OFF

Article number: N007-K0001-RF927-H5-M15-ZE51_650-S1-###





LED	COB	Spotlig
Light colour	2700 [K]	Compa installat colour a 60°. Ma
CRI	80	
Led chip flux	2888 [lm]	
Luminous flux	2599 [lm]	
System power	25 [W]	
Luminaire Efficiency	104 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,85 [kg]

GREY

Plastic

IP 20, IK 1,

220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base nstallation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska SPOTLIGHT

