

SPOTLIGHT LIDER B MINI 927 27W 60° GREY | ON/OFF

Article number: N007-K0001-RF927-H5-M60-ZE51_700-S1-###





| LED | COB | Spotlight LED |
|----------------------|------------|---|
| Light colour | 2700 [K] | Compact track n installation possi colour available 60°. Maximum p |
| CRI | 80 | |
| Led chip flux | 3111 [lm] | |
| Luminous flux | 2799 [lm] | |
| System power | 27 [W] | |
| Luminaire Efficiency | 104 [lm/W] | |
| Beam angle | 60° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | _ |
| Weight | 0,85 [kg] | |
| | | |

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

mounted LED spotlight. Aluminium housing. Ceiling base sible. Available in white, black and grey. Any RAL palette e on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT

