

SPOTLIGHT LIDER B MINI 930 21W 23° GREY | ON/OFF

Article number: N007-K0001-RF930-H5-M23-ZE51_550-S1-###



IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic



LED	COB	Spotl
Light colour	3000 [K]	Comp install colour 60°. N
CRI	90	
Led chip flux	2536 [lm]	
Luminous flux System power	2282 [lm] 21 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	23°	
Controller MacAdam	ON/OFF 3 SDCM	
UMINAIRE		_
LOMINAIRE		
Weight	0,85 [kg]	

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base nstallation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 50°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

L

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska SPOTLIGHT