

SPOTLIGHT LIDER B MINI 930 19W 38° GREY | ON/OFF

Article number: N007-K0001-RF930-H5-M38-ZE51_500-S1-###





LED	COB	Spotlight LED
Light colour	3000 [K]	Compact track m installation possit colour available o 60°. Maximum po
CRI	90	
Led chip flux	2305 [lm]	
Luminous flux	2074 [lm]	
System power	19 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

nounted LED spotlight. Aluminium housing. Ceiling base sible. Available in white, black and grey. Any RAL palette on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT