

## SPOTLIGHT

## SPOTLIGHT LIDER B MINI 825 19W 15° GREY BREAD ON/OFF

Article number: N007-K0001-VF825-H5-M15-ZE51\_500-S1-###





CRI 80 insta <sup>l</sup> lation possible. Av colour available on eng	LED	COB	Spotlight LED
CRI 80 colour available on end 60°. Maximum power is   Led chip flux 2340 [Im]   Luminous flux 2106 [Im]   System power 19 [W]   Luminaire Efficiency 111 [Im/W]   Beam angle 15°   Controller ON/OFF   MacAdam 3 SDCM	Light colour	2500 [K] BREAD	Compact track mounted L installation possible. Avai colour available on enqui 60°. Maximum power is 2
Led chip hux2340 [hin]Luminous flux2106 [lm]System power19 [W]Luminaire Efficiency111 [lm/W]Beam angle15°ControllerON/OFFMacAdam3 SDCM	CRI	80	
System power 19 [W]   Luminaire Efficiency 111 [Im/W]   Beam angle 15°   Controller ON/OFF   MacAdam 3 SDCM	Led chip flux	2340 [lm]	
Luminaire Efficiency 111 [Im/W]   Beam angle 15°   Controller ON/OFF   MacAdam 3 SDCM	Luminous flux	2106 [lm]	
Beam angle 15°   Controller ON/OFF   MacAdam 3 SDCM	System power	19 [W]	
Controller ON/OFF MacAdam 3 SDCM	Luminaire Efficiency	111 [lm/W]	
MacAdam 3 SDCM	Beam angle	15°	
LUMINAIRE	Controller	ON/OFF	
	MacAdam	3 SDCM	
Weight 0,85 [kg]	LUMINAIRE		
	Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

LED spotlight. Aluminium housing. Ceiling base ailable in white, black and grey. Any RAL palette uiry. Reflector beams available: 15°, 23°, 38°, 45° and 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska