

SPOTLIGHT

SPOTLIGHT LIDER B MINI 930 19W 15° BLACK CRI97 ON/OFF

Article number: N007-K0002-HI930-H5-M15-ZE52_500-S1-###





LED	COB	Spotlight LED
Light colour	3000 [K] CRI97	Compact track mo installation possib colour available or 60°. Maximum por
CRI	90	
Led chip flux	2199 [lm]	
Luminous flux	1979 [lm]	
System power	19 [W]	
Luminaire Efficiency	104 [Im/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,85 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz

nounted LED spotlight. Aluminium housing. Ceiling base ible. Available in white, black and grey. Any RAL palette on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and ower is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska